





PX プーリ / 品種・形式一覧



プーリ品種・形式一覧

● P5M

単位：mm

歯数 n	ピッチ円 直径 Dp	歯先円 直径 Do	フランジ 外径 Df	ハブ 直径 Dh	対象 形式	軸穴径 加工可能 範囲	P5M10				P5M15				P5M25			
							AF		BF		AF		BF		AF		BF	
							Bw	L	Hw	L	Bw	L	Hw	L	Bw	L	Hw	L
16	25.46	24.32	31	17	AF・BF	10	16	8	12	6	21	10.5	12	6	32	16	12	6
18	28.65	27.51	36	19	AF・BF	10~11	16	8	12	6	21	10.5	12	6	32	16	12	6
20	31.83	30.69	36	19	AF・BF	10~11	16	8	12	6	21	10.5	12	6	32	16	12	6
22	35.01	33.87	43	25	AF・BF	10~15	16	8	12	6	21	10.5	12	6	32	16	12	6
24	38.20	37.06	44	25	AF・BF	10~15	16	8	12	6	21	10.5	12	6	32	16	12	6
25	39.79	38.65	45	30	AF・BF	10~18	16	8	12	6	21	10.5	12	6	32	16	12	6
26	41.38	40.24	47	30	AF・BF	10~18	16	8	12	6	21	10.5	12	6	32	16	12	6
28	44.56	43.42	52	32	AF・BF	10~21	16	8	12	6	21	10.5	12	6	32	16	12	6
30	47.75	46.60	55	35	AF・BF	12~23	16	8	12	6	21	10.5	12	6	32	16	12	6
32	50.93	49.79	55	38	AF・BF	12~25	16	8	12	6	21	10.5	12	6	32	16	12	6
36	57.30	56.15	64	44	AF・BF	12~29	16	8	12	6	21	10.5	12	6	32	16	12	6
40	63.66	62.52	67	48	AF・BF	12~32	16	8	12	6	21	10.5	12	6	32	16	12	6
44	70.03	68.89	74	56	AF・BF	15~37	16	8	12	6	21	10.5	12	6	32	16	12	6
48	76.39	75.25	82	58	AF・BF	15~39	16	8	12	6	21	10.5	12	6	32	16	12	6
50	79.58	78.44	86	64	AF・BF	15~43	16	8	12	6	21	10.5	12	6	32	16	12	6
60	95.49	94.35	103	80	AF・BF	15~53	16	8	12	6	21	10.5	12	6	32	16	12	6
72	114.59	113.45	120	90	AF・BF	18~60	16	8	12	6	21	10.5	12	6	32	16	12	6

● P8M

単位：mm

歯数 n	ピッチ円 直径 Dp	歯先円 直径 Do	フランジ 外径 Df	ハブ 直径 Dh	対象 形式	軸穴径 加工可能 範囲	P8M15				P8M25				P8M40				P8M60			
							AF		BF		AF		BF		AF		BF		AF		BF	
							Bw	L	Hw	L	Bw	L	Hw	L	Bw	L	Hw	L	Bw	L	Hw	L
20	50.93	49.56	55	36	AF・BF	12~24	22	11	17	8.5	33	16.5	17	8.5	49	24.5	17	8.5	70	35	17	8.5
22	56.02	54.65	62	41	AF・BF	12~27	22	11	17	8.5	33	16.5	17	8.5	49	24.5	17	8.5	70	35	17	8.5
24	61.12	59.74	66	46	AF・BF	12~31	22	11	17	8.5	33	16.5	17	8.5	49	24.5	17	8.5	70	35	17	8.5
26	66.21	64.84	73	51	AF・BF	16~34	22	11	17	8.5	33	16.5	17	8.5	49	24.5	17	8.5	70	35	17	8.5
28	71.30	69.93	79	55	AF・BF	16~37	22	11	17	8.5	33	16.5	17	8.5	49	24.5	17	8.5	70	35	17	8.5
30	76.39	75.02	82	60	AF・BF	16~40	22	11	17	8.5	33	16.5	17	8.5	49	24.5	17	8.5	70	35	17	8.5
32	81.49	80.12	86	65	AF・BF	16~43	22	11	17	8.5	33	16.5	17	8.5	49	24.5	17	8.5	70	35	17	8.5
34	86.58	85.21	91	70	AF・BF	16~47	22	11	17	8.5	33	16.5	17	8.5	49	24.5	17	8.5	70	35	17	8.5
36	91.67	90.30	97	75	AF・BF	16~50	22	11	17	8.5	33	16.5	17	8.5	49	24.5	17	8.5	70	35	17	8.5
40	101.86	100.49	107	85	AF・BF	20~57	22	11	17	8.5	33	16.5	17	8.5	49	24.5	17	8.5	70	35	17	8.5
44	112.05	110.67	119	90	AF・BF	20~60	22	11	22	11	33	16.5	22	11	49	24.5	22	11	70	35	22	11
48	122.23	120.86	127	100	AF・BF	20~67	22	11	22	11	33	16.5	22	11	49	24.5	22	11	70	35	22	11
50	127.32	125.95	135	100	AF・BF	20~67	22	11	22	11	33	16.5	22	11	49	24.5	22	11	70	35	22	11
60	152.79	151.42	158	100	AF・BF	20~67	22	11	22	11	33	16.5	22	11	49	24.5	22	11	70	35	22	11
64	162.97	161.60	167	110	AF・BF	20~73	22	11	22	11	33	16.5	22	11	49	24.5	22	11	70	35	22	11
72	183.35	181.97	190	110	AF・BF	30~73	22	11	22	11	33	16.5	22	11	49	24.5	22	11	70	35	22	11

● P14M

単位：mm

歯数 n	ピッチ円 直径 Dp	歯先円 直径 Do	フランジ 外径 Df	ハブ 直径 Dh	対象 形式	軸穴径 加工可能 範囲	P14M40				P14M60			
							AF		BF		AF		BF	
							Bw	L	Hw	L	Bw	L	Hw	L
28	124.78	121.98	136	90	AF・BF	20~60	53	26.5	20	10	74	37	20	10
30	133.69	130.90	145	100	AF・BF	20~67	53	26.5	20	10	74	37	20	10
32	142.60	139.81	154	110	AF・BF	20~73	53	26.5	20	10	74	37	20	10
34	151.52	148.72	163	120	AF・BF	20~80	53	26.5	20	10	74	37	20	10
36	160.43	157.63	171	120	AF・BF	20~80	53	26.5	20	10	74	37	20	10
38	169.34	166.55	181	135	AF・BF	20~80	53	26.5	20	10	74	37	20	10
40	178.25	175.46	190	135	AF・BF	20~80	53	26.5	20	10	74	37	20	10
42	187.17	184.37	198	135	AF・BF	20~80	53	26.5	20	10	74	37	20	10
44	196.08	193.28	207	155	AF・BF	20~80	53	26.5	25	12.5	74	37	25	12.5
48	213.90	211.11	225	160	AF・BF	20~80	53	26.5	25	12.5	74	37	25	12.5
50	222.82	220.02	234	160	AF・BF	20~80	53	26.5	25	12.5	74	37	25	12.5